

1710-2170MHz Dual Polarization Manual Tilt Panel Antenna

Electrical Specifications

Frequency Range	1710 - 2170 MHz
Gain	20 dBi GSM1800, 21 dBi UMTS
Return Loss	> 14 dB
Polarization	Dual Slant $\pm 45^\circ$
Horizontal Beamwidth	32°
Vertical Beamwidth	5.5° with nullfill
Electrical Downtilt	0° - 10° continuously adjustable
Upper Sidelobe Level	< -16 dB
Front to Back Ratio	> 30 dB
Isolation Between Ports	> 30 dB
Power Rating	300W
Intermodulation	< -150 dBc (2 x 43 dBm)
Impedance	50 ohm
Lightning Protection	DC grounded
Connector Type	7-16 DIN female



Mechanical Specifications


Antenna Dimensions	1600x300x110 mm
Packed Dimensions	1730x330x205 mm
Antenna Weight	13 kg
Radome Material	PVC

Maximum Environmental Ratings


Humidity	95% RH @ 30°C
Lateral Loading (Front)	0.67 kN @ 160 km/h
Lateral Loading (Rear)	0.73 kN @ 160 km/h
Rain	140mm per hour
Rated Wind Velocity	200 km/h
Temperature	-40°C to +70°C

Mounting Options

F-042-GL-E	Fixed clamp
T-029-GL-E	Adjustable clamp



Azimuth



Elevation

Last Updated: 24-06-2008



Argus Technologies (Australia) Pty Ltd

10-12 Lexington Drive, Northwest Business Park, Bella Vista NSW 2153 Australia

T +61 2 8884 0888 F +61 2 8884 0882 E info@argusantennas.com W www.argusantennas.com

Argus Technologies is continually improving products. Specifications may change at any time without notice